

DUST MONKEY DFS

WWW.DUSTMONKEY.NET

SPECIFICATIONS

The brand new DF/S model portable fan is suitable for the suction of fumes, gases, dusts, polluted air, small pneumatic transport of light dusts, and air blowing. It is suitable in all that cases where a quick solution or a simple and flexible installation of an extraction fan is required. Thanks to the minimum weight and dimensions, the DF/S unit can be easily carried, is very practical, and extremely handy for use in a variety of demanding environments. The DF/S is also equipped with a special support so that it can be positioned in any direction, which helps make the fan more useful in different



situations. The special centrifugal electro-fan with open blades impellor, built in painted steel, allows an excellent suction also with a flexible hose of considerable length. The DF/S unit complete with

protection grate on air inlet and outlet is supplied normally in single-phase, 220 V version. with ON/OFF switch on the motor or three-phase, 220/380 V version. A hose may be attached to the fan to assist with extraction of fumes or dusts at a specific source.

FEATURES

- * The brand new DF/S model portable fan is suitable for the suction of fumes, gases, dusts, polluted air, small pneumatic transport of light dusts, and air blowing.
- * Equipped with a special support so that it can be positioned in any direction.
- * Allows for a great amount of suction with a flexible hose of considerable length.

OPTIONS

- * Flexible hose Ø 3", 4", 5", 6", or 7" for welding fumes or dusts.
- * Flexible hose clamps Ø 3", 4", 5", 6", or 7".
- * Reduction cones Ø 3", 4", 5", 6", or 7".
- * Couplings Ø 3", 4", 5", 6", or 7".
- * A-type (rough dusts) or B-type (fine dusts) felt filtering bag (rough dusts) Ø 12" with a length of 2.5 feet
- * Filtering bag clamp Ø 12"

DIMENSIONS, ETC.

Dust Monkey products are manufactured in metric sizes but described here and on the web site in their closest English equivalent. Representative sizes and dimensions are described here. Custom sizes and materials are available.

Diameters:
63 mm: 2.5 inches
75 mm: 3 inches
100 mm: 4 inches
125 mm: 5 inches
160 mm: 6 inches
200 mm: 8 inches

Lengths:
1.5m: 5 feet
2.0m: 6 feet
3.0m: 10 feet
4.0m: 13 feet
5.0m: 16 feet
6.0m: 20 feet
7.0m: 23 feet
8.0m: 26 feet
9.0m: 30 feet

WWW.DUSTMONKEY.NET

Komodo Enterprises, Inc. DBA
Dust Monkey
2620 S. Maryland Pkwy
Suite 14, Box 863
Las Vegas, NV 89109

California Office
8915 Research Dr.
Irvine CA, 92618

Tel: 949.341.0314
Fax: 949.341.0315

E-mail: info@dustmonkey.net



*Tough, Durable,
Rugged, Reliable,
Stout Construction*

Visit all our web sites:
WWW.DUSTMONKEY.NET
WWW.DUCTMONKEY.NET
WWW.MONKEYARMS.COM



*Experts in Dust, and
Fume Control.*

WWW.DUSTMONKEY.NET

MODELS AVAILABLE

ET	FAN			MOTOR	TOTAL PRESSURE (INCHES OF H2O)								WEIGHT (LB)	
	POWER (HP)	RPM	SOUND LEVEL dB(A)		0.20	0.39	0.59	0.79	1.18	1.57	1.97	2.36		
10	0.12	900	50	63A6	41	24								35
10	0.16	1400	57	63A4	60	45	41	30						35
20	0.16	900	52	63A6	60	26								48
20	0.24	1400	64	63B4	90	67	60	51	41					48
30	0.24	900	59	71A6	86	52	41							68
30	0.33	1400	69	71A4	127	105	97	90	71	64				68
40	0.24	900	60	71A6	123	122	67	56						79
40	0.67	1400	72	80A4	187	161	150	138	116	94	86			79
50	0.33	900	65	71B6	176	127	105	86	75					101
50	1	1400	75	80B4	283	244	224	207	183	161	144	114		101
60	0.24	700	60	80B8	181	114	79							121
60	0.47	900	68	80A6	187	209	171	152	114					
60	2	1400	78	90L4	417	362	323	303	283	246	228	191		143
70	0.47	700	61	90S8	248	173	142	110						156
70	1	900	69	90S6	374	303	268	236	189	154				156
80	0.67	700	65	90L8	362	248	209	189	130					209
80	2	900	72	100L6	531	437	398	362	303	248	209			209
90	1.47	700	68	100LB8	511	362	323	283	228	189				235
90	2.95	900	75	112M6	744	630	575	535	480	421	366	307		235

WWW.DUSTMONKEY.NET

Komodo Enterprises, Inc. DBA
Dust Monkey
2620 S. Maryland Pkwy
Suite 14, Box 863
Las Vegas, NV 89109

California Office
8915 Research Dr.
Irvine CA, 92618

Tel: 949.341.0314
Fax: 949.341.0315

E-mail: info@dustmonkey.net



*Tough, Durable,
Rugged, Reliable,
Stout Construction*

Visit all our web sites:
WWW.DUSTMONKEY.NET
WWW.DUCTMONKEY.NET
WWW.MONKEYARMS.COM



*Experts in Dust, and
Fume Control.*

TERMS AND CONDITIONS

PAYMENTS AND TERMS

Prices quoted are good for 30 days unless otherwise noted. Dust Monkey accepts cash, check, wire transfer, or credit cards. All prices are quote in US Dollars, unless otherwise noted. All sales are final. All freight is FOB, Las Vegas, Nevada unless otherwise noted. All goods remain the property of Dust Monkey until paid in full. Payment is due at time of order unless credit has been granted. All past due accounts accrue a service fee of 3% per month. Dust Monkey is a DBA of Komodo Enterprises, Inc., a Nevada Corporation.

PRIVACY STATEMENT

Komodo Enterprises Inc. respects your privacy and will not divulge your contact information to any third party organization or entity without your express permission. In addition, our web sites gather no unauthorized information from your computer during your visit with us. All phone calls to Dust Monkey may be monitored or recorded.

ACCURACY

Dust Monkey assumes no responsibility for errors or omissions in this web site or documents which are referenced by or linked to this site. This site could include technical or other inaccuracies. Changes are periodically added to the information, and Dust Monkey may change the products or services described at any time. Contact Customer Service for further information before relying on any information contained herein. The information provided on this site, including text, images, and links, are provided "AS IS" by Dust Monkey solely as a convenience to its visitors. This information is without any warranties, express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose or non-infringement.

WARRANTY & INDEMNITY

Dust Monkey warrants products it manufactures for a period of 90 days to the original purchaser from the date of purchase. Items not manufactured by Dust Monkey are limited to their own manufacturer's warranties. This warranty does not apply to defects due directly or indirectly to misuse, negligence, accidents, abuse, repairs, or alterations or lack of maintenance. This is Dust Monkey's sole written warranty and any and all warranties that may be implied by law, including any merchantability or fitness, for any particular purpose, are hereby limited to the duration of this written warranty. Dust Monkey does not warrant or represent that the merchandise complies with the provisions of any law or acts. In no event shall Dust Monkey liability under this warranty exceed the purchase price paid for the product. Both parties agree to binding arbitration in Las Vegas, Nevada. Dust Monkey shall in no event be liable for death, injuries to persons or property or for incidental, and contingent, special, or consequential damages arising from the use of our products. Dust Monkey warrants products only for the specific use expressly agreed to at time of purchase by Dust Monkey in writing. Motors should only be started and stopped up to 4 - 10 times per hour. Starting motors more frequently can cause heat build up and can cause the motor overload to trip or cause motor damage. In general, motors should be started and stopped as little as possible for maximum lifespan and best economy (electrical use). *Note: Motors should be protected from extreme weather to prolong motor life. All claims, including claims covered under the limited warranty, are subject to inspection and investigation before Buyer's claim is settled. Any parts returned for warranty or repair will not be accepted without an RMA number and must be shipped pre-paid. Contact Customer Service with the original bill of sale to obtain an RMA number.

WWW.DUSTMONKEY.NET